



# SA106D-05HS

## 6W Switching Adapter

### Input

Rated Voltage	100 - 240 VAC
Max. Voltage	90 - 264 VAC
Line Frequency	47 - 63 Hz
Current	250mA at 100-240VAC
Configuration	CCC -2PIN

### Output

Model Name	Voltage	Current	Watt	Efficiency
SA106D-05HS	5V	1.2A	6W	60%

Line Regulation	Less than $\pm 2\%$
Load Regulation	Less than $\pm 5\%$
Protections	OCP, OVP & SCP
Ripple & Noise	$\leq 100\text{mVp-p}$

### Environment

Operating Temp.	0°C - 40°C
Storage Temp.	-20°C - 80°C
Humidity	10% - 90% (Non-condensing)
RoHS & WEEE	Standard

### Reliability

MTBF	50,000 hrs (by MIL-217 Standard)
Safety	ITE: CCC

### Others

Package	100 pcs/box
Min. Order	1K pcs/lot
Warranty	1 year

For reference only. For details please contact your local sales representative

### Electrical

Topology	Switching Mode
Hi-Pot	3000 Vac/1sec @ 5mA (primary - secondary)
Leakage Current	$\leq 0.25\text{mA}$ , at 264VAC/50Hz
Hold Up Time	$\geq 6$ mSec
Standby Power	$\leq 0.3$ Watt (As per ErP Guideline)
Consumption	Guideline)
EMI	Complies with EMI directives
Energy Star Requirement	EPS 2.0 (Efficiency Level V)

### Mechanical

Case Size	64L x 45W x 31H mm
Case Material	Black, 94V-1 or equivalent
Weight	90 $\pm 5$ g
DC Cord	4.92ft

